







Make
The
Right
Connection.

www.hagemann-systems.de info@hagemann-systems.de







Lugsulation© Flex

- · for protruding contacts
- sealing axially in the direction of the screw
- application possible with insulated plastic headed bolt screw or cap nut
- connection of multiple cables possible with the use of a copper space ring
- protection class up to IP64 (certified)
- a higher protection class up to IP66 is possible with certain measures
- as example Flex can be used in European traction batteries according to DIN and British standard
- sealing internal and external threads
- available from 10-120mm²

Lugsulation© Deep

- 100 % contact on flat terminals due to the deep pressed cable lug
- the higher level of the cable lug allows circumferential, mainly radially insertable seal
- protection class up to IP64
- Deep is used as an example in switch cabinet constructions
- sealing internal & external threads
- Deep is available in the "cap" version
- available in 35mm² M6 (other sizes only with large order quantity)





Lugsulation© Seal

- terminal screws or connection areas are also insulated
- perfectly suited for humid/saltwater environments
- the sealing area completely insulates the contact
- depending on the requirements, the sealing area can be designed radially as a lip, axially as a tube, or as a combination of both sealing directions
- protection class up to IP64
- Lugsulation Seal in the "cap"-version for example can be used for inverters
- sealing internal and external threads
- available in 35mm² M5 & M8 (other sizes only with large order quantity)

Lugsulation© Cap

- all Lugsulation variants are available in the cap version
- the main feature is the use of an Allen screw (ISK)
- is usually used when there is little space for installation
- the cylindrical head seals radially i.e., circumferentially to the direction of screwing – against its inner wall
- as an example, this variant can be used in narrow engine compartments of agricultural machinery
- protection class up to IP64
- suitable for sealing internal threads
- available in 50mm² M10 (other sizes only with large order quantity)

Lugsulation© Flex



Lugsulation© Seal

Lugsulation© Cap

connection type









further applications







half section









sealing under sight







